



CE certified product
(DIN EN 13561: 2009-01)



All-year-round use



Wind-dynamic due
free-floating
suspension

(Resistance to wind load
– class 3
tested according to
DIN EN 13561: 2009-01)



High UV Protection
UPF 50+



Rainproof, water runs off
automatically from an
inclination of 8+ degrees

(Resistance to water
accumulation –
class 2 according to DIN EN
13561)

SHADESIGN GmbH

Bruckmühler Straße 29 | D - 83052 Bruckmühl - Heufeld | Phone: +49 (0) 8061 989 45 - 0
info@shadesign.com | www.shadesign.com

For (printing) errors and omissions no liability is assumed. Subject to technical modifications.

V2024.01



Passion for shade



SHADECUBE

Rollable Sail in
freestanding, puristic
CUBE construction

Awning were yesterday!

SHADE shadow systems
The original since 2012



Passion for shade

SHADE^{CUBE}

Free standing version as sun and rain protection

PURISTIC, FREESTANDING AND SELFSUPPORTING with its slimline design, the **SHADE^{CUBE}** is a real eyecatcher. The textile membrane's integrated height adjustment not only offers protection from the setting sun, but also facilitates controlled water drainage.

A wall connection for the **SHADE** shadow-system is not required with this system type.



Benefits **SHADE^{CUBE}**

- **Filigree design** for maximum wind stability
- **Easy assembly** – fully pre-assembled system, plug-in and bolted frame
- **Fully waterproof sail membrane** – Bonded panels
- **Controlled water drainage in the rain** with one-sided height adjustment
- **34,5 m² maximum surface area per CUBE** – extendable from all sides

Delivery range for **SHADE^{CUBE}**

- **Complete made-to-measure SHADE-Sail**
- **Height adjustment (standard):** 1-part crank lever height adjustment (right or left option) included in basic price
- **Roll-up canopy** included in basic price (avail. colours: Silver (similar to RAL 9006/ Anthracite (similar to NSC S7500-N))
- **Stainless steel frame construction** (square tube 60 / 60 / 2 – brushed stainless steel)
- **4-part base fixing plates** (150 x 150 x 6 mm – brushed stainless steel)

Technology **SHADE^{CUBE}**

- | | |
|-------------------------------------|--------|
| • Maximum equipment width | 600 cm |
| • Maximum overhang | 600 cm |
| • System height (min.) | 248 cm |
| • System height (max.) | 280 cm |
| • Drive mechanism (standard) | Manual |

Surcharge for **SHADE^{CUBE}**

- **Console rail continuous**
Cut to system width | No calculatory deduction of the wall/ceiling brackets | Available in Colours: White (RAL 9016), White aluminium (RAL 9006) & Anthracite (RAL 7016)
- **Second crankable height adjustment (standard, angular)**
- **Radio motor incl. transmitter**
- **RAL special colour**
(CUBE stainless steel frame incl. 4 columns & base plates)

